



Wire strapping buckles



Material : steel
Surface : electro-galvanized or phosphated

Specifications:

Item No.	Size (+/- 1 mm)	Wire Diameter	Breaking Strength (kg +/- 5 %)	Weight / Box	PCS / Box	Boxes / Pallet (1050 x 1050 mm)
WSB1330	13 mm	3.0 mm	480 kg	8.0 kg	1,000	96
WSB1333	13 mm	3.3 mm	480 kg	9.8 kg	1,000	96
WSB1633	16 mm	3.3 mm	680 kg	11.5 kg	1,000	84
WSB1635	16 mm	3.5 mm	880 kg	12.3 kg	1,000	84
WSB1940	19 mm	4.0 mm	760 kg	18.0 kg	1,000	72
WSB1945	19 mm	4.5 mm	1,000 kg	11.8 kg	500	84
WSB2550	25 mm	5.0 mm	1,256 kg	17.4 kg	500	72
WSB2560	25 mm	6.0 mm	1,480 kg	14.0 kg	250	84
WSB3260	32 mm	6.0 mm	1,800 kg	16.0 kg	250	84
WSB3270	32 mm	7.0 mm	2,600 kg	21.8 kg	250	60
WSB4070	40 mm	7.0 mm	3,200 kg	21.5 kg	200	60
WSB4080	40 mm	8.0 mm	3,500 kg	28.0 kg	200	48

Remarks:

- Wire buckles must be stored in dry conditions.
- Over-tensioning may damage the wire buckles and / or the straps.
Stop tensioning once the buckle closes from both ends.

(Important note: Measures and weights without engagement. We reserve the right to change technical details.)