

# HMPE lashing rope - 19 mm



#### **Characteristics:**

- Good abrasion resistance
- Low weight (7x lighter than steel)
- Good stability with respect to UV light
- Resistant to chemicals
- Easy handling
- Easy to splice and inspect
- Has the same strength wet or dry
- The length remains same under wet conditions
- It stores very little energy, therefore has little backlash if it breaks, improving safety

### **Construction:**

12-Strand





## Specifications:

Rope diameter	Rope length	MBL	Eye length	Weight per m		Length tolerance	Eye color	Color marking	Weight per pc	
mm	m	kN	m	kg / m	tolerance	cm		splice cover	kg	tolerance
19	1.5	- 240	0.25	0.20	5 %	±5	Red	Red	0.8	±5%
	2.0							Orange	0.9	
	3.0							Yellow	1.1	
	4.0							Green	1.3	
	5.0							Blue	1.5	
	6.0							Black	1.7	
	10.0							Purple	2.5	
	15.0							Gray	3.5	

(Important note: Measures and weights without engagement. We reserve the right to change technical details.)

Stuut Lifting & Lashing - SLL Handelsvertretung e. K. sales@marine-lashing.com +49 5228 9628290

#### Material and performance:

- High quality UHMWPE fiber
- Specific gravity: 0.975
- Melting point: 150° C
- Water absorption: none
- UV resistance: high
- Abrasion resistance: high